

K-2 SLIDE GATE OPERATOR



RESIDENTIAL

CLASS I VEHICULAR SLIDE GATE OPERATOR



LCD DIAGNOSTICS DISPLAY
 - Displays full error messages
 - Reads real-time voltages and settings

DIGITAL LIMITS

REMOVABLE POWER SUPPLY
 - Convenient fuse access
 - L.E.D status indicators
 - Convenient power switch
 - E-Z access power outlet
 - E-Z set up 115V/230V
 - Included low voltage option

V FLEX CONTROL BOARD
 - Conveniently labeled enclosure
 - Ergonomically located

BUILT-IN HEATER
 - Cold weather operation
 down to -20° F

NEW REDESIGNED CHASSIS

COMPATIBLE WITH VIKING WIRELESS PRODUCTS

- Plug & Play connection for the Viking wireless expansion products.
- Viking Konnect - Wireless Kit provides secure and reliable wireless communication when the application requires two single ECUs.
- Viking Monitor - Remote access to the control board settings, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible hand held device

BATTERY BACKUP INCLUDED

- Standard Battery Backup provides 100 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.

LIGHTNING PROTECTION

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps
- On-board surge protection monitoring.

DIGITAL LIMITS

- Simple, push button limit setup.
- Adaptive Digital Limit control maintains open and close limit position during changing environments and power failures.

INTEGRATED HEATER

- Built-in heater for operating temperatures down to -20° F.
- This will allow you run your operator in the coldest conditions.

SOLAR SMART

- Power Saving technology minimizes current draw while at standby.

DIAGNOSTICS DISPLAY

- On-board LCD screen displays voltages, amps, gate status and diagnostics.

Operational Voltage	24 VDC
Main Power Source Options	120/240 VAC Single Phase
Battery	12 VDC x 2
Battery Backup	100 Full Contin. Cycles (700 lbs)

Operating Speed	12" per Second
Operating Temperature	-20° F up to +160° F
Max Gate Capacity	700 lbs/ 30'
Max Duty Cycle	100% Contin. Cycle